

Product No: 942 300-006

HIRSCHMANN NEXT-GENERATION FIREWALL WITH STATEFUL PACKET INSPECTION 2X GE TX, 1X GE SFP, 24-48V DC, -40-70°C, UL APPROVAL, WITH INDUSTRIAL PROTECTION SUITE 942300006



FEATURES

- Next-Generation Firewall with Stateful Packet Inspection
- IPSec VPN
- SW Version 04.3.
- Deep Packet Inspection

General Information

Brand	HIRSCHMANN
Product Type	Industrial Router

Technical Attributes

Operating Voltage	2 x 24/36/48V DC
Port Quantity and Type	2 x TX + 1 x SFP
Power Consumption (W)	Max. 15
Power Output in BTU (IT)/h	51

Physical Attributes

Housing Material	Rugged high-strength sheet
Mounting Type	Din Rail Mount
Operational Temperature Range (°C)	-40 to +70
Relative Humidity	10-95 %
Storage Temperature Range (°C)	-40 to +85

Dimensions

Dimensions (mm)	70W x 187.2H x 135.8D
Weight (kg)	1.96

Protection & Standards

Approvals	CE, FCC, EN 61131
-----------	-------------------

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------