

Product No: DVM2TNC255FM

DEHN SPD T1+T2+T3, 3P+PEN In=25kA WITH C/O CONTACT DVM2TNC255FM

FEATURES

- - Compact unit
- - Maximum safety with Rapid Arc Control (RAC)
- - Capable of protecting terminal equipment
- - Standards IEC/EN 61643-11



General Information

Article No.	954305
Brand	DEHN
Product Type	Surge Protection Device

Technical Attributes

Circuit Type	MSB
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	25 (L-PEN)
Maximum Continuous Operating Voltage MCOV AC (V)	255
No. of Poles	3P+PEN
Nominal Discharge Current (8/20 μ s) - In (kA)	25
Nominal Voltage AC (V)	230/400
Operating State/Fault Indication	Green/Red
Response Time (ns)	≤ 100
Short-Circuit Withstand Capability - I _{sc} (kArms)	50
Signal C/O Contact	Yes
SPD Type	Type 1 + Type 2 + Type 3

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

No. of Modules	4
----------------	---

Protection & Standards

Degree of Protection

IP20

Resources

Product catalogue (Flipbook)

[Download from here](#)