

Product No: NF22E12

CTR RELAY 2 NO 2 NC, 48..130VC OIL

FEATURES

- Type: 4-pole contactor relay
- Voltage Ratings: 690 V (IEC), 600 V (UL)
- Usage: Switching auxiliary and control circuits
- Control Voltage Range: 48-130 V (50/60 Hz and DC)



General Information

Product Type	NF Contactor Relay
--------------	--------------------

Technical Attributes

Rated Control Circuit Voltage AC (V)	50 Hz 48 ... 130 V 60 Hz 48 ... 130 V DC Operation 48 ... 130 V
Rated Impulse Withstand Voltage (kV)	6
Rated Operational Current AC-15 (A)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Operational Current DC-13 (A)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Voltage AC (V)	690
Terminal Type	Screw Terminals