

## ABB E12N3ETG12W ACB E1.2N 3P 66KA WITHDRAWABLE 1250A EKIP TOUCH LSIG

E12N3ETG12W



### GENERAL INFORMATION

Brand	ABB
Product Type	Automatic
Version	Withdrawable

### TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - I <sub>cu</sub> (kA)	66
G (0.1 to 1 x I <sub>n</sub> ) - I <sub>4</sub> (A)	125-1250
I (1.5 to 15 x I <sub>n</sub> ) - I <sub>3</sub> (A)	1875-18750
L (0.4 to 1 x I <sub>n</sub> ) - I <sub>1</sub> (A)	500-1250
No. of Poles	3P
Power Loss (W)	244
Rated Current (A)	1250
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/1s)	50
Rated Uninterrupted Current - I <sub>u</sub> (A)	1250
S (0.6 to 10 x I <sub>n</sub> ) - I <sub>2</sub> (A)	750-12500
Terminal Type	HR-HR
Trip Unit	EKIP Touch LSIG

## DIMENSIONS

Frame Size	E1.2
------------	------

---

## PROTECTION & STANDARDS

Standards and Approvals	IEC
-------------------------	-----

---

## RESOURCES

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------

---