

Product No: B7220001

ABB B7-22-00-01 MINI CONTACTOR 24 V AC - 2 NO - 2 NC -SCREW TERMINALS B7220001

FEATURES

- Space saving contactor with screw terminals
- Ensures high reliability, making it suitable for residential, commercial and industrial use
- Controls single or three phase loads, ideal for diverse applications
- Noiseless and hum-free coil for quiet operation
- Integrated features for easy rail or wall mounting, providing flexibility in installation



General Information	
Brand	ABB
Product Type	Mini Contactor

Technical Attributes	
Actuating Voltage Type	AC
Auxiliary Contacts	2NO/2NC
Main Circuit Electrical Connection	Screw Connection
No. of Normally-closed Contacts	2
No. of Normally-open Contacts	2
No. of Poles	4
Operating Voltage AC (V)	220
Power Loss (W)	1.4/pole AC-1
Rated Control Circuit Voltage AC (V)	24
Rated Control Supply Voltage AC (V)	24
Rated Control Supply Voltage DC (V)	24
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	690
Rated Operational Current AC-1 240V (A)	20
Rated Operational Current AC-1 690V (A)	6
Rated Operational Power AC-3 400V (kW)	5.5
Rated Operational Power AC-3 415V (kW)	5.5



Technical Attributes	
Rated Operational Voltage AC (V)	220
Rated Supply Voltage AC (V)	24
Terminal Type	Screw

Physical Attributes	
Mounting Type	DIN Rail / Wall
Operational Temperature Range (°C)	-25 to +55

Dimensions	
Dimensions (mm)	52.5W x 57.5H x 46.7D

Protection & Standards	
Degree of Protection	IP20

Resources

Product catalogue (Flipbook)

Download from here