

## Product No: 101059049

### SCHMERSAL MK 461-22YMEDIUM-DUTY POSITION SWITCH 101059049



#### General Information

Brand	SCHMERSAL
-------	-----------

#### Technical Attributes

Switchover Time (ms)	35ms (Maximum)
Actuating Angle	45° - From Left of Switch Axis, 30° - From Right of Switch Axis
Actuating Element	Offset Roller Lever
Contact Material	Silver
Maximum Actuating Speed (m/s)	0.5
Maximum Bounce Duration (ms)	5
Maximum Cable Cross Section (mm <sup>2</sup> )	2.5
Maximum Fuse Rating	16 A gG D-fuse
Minimum Actuating Speed (mm/min)	1
Minimum Cable Cross Section (mm <sup>2</sup> )	1.5
Minimum Mechanical Life	5000000 Operations
No. of Normally-closed Contacts	2
No. of Normally-open Contacts	2
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	250
Rated Operational Current AC-15 (A)	4
Rated Operational Voltage AC-15 (V)	230V AC
Switching Element	NO Contact / NC Contact

Termination	Screw Terminals M20 x 1.5
Thermal Test Current (A)	16
Utilisation Category	AC-15

### Physical Attributes

Castor Material	Plastic
Contact Opening (mm)	2 x 2.5
Enclosure Coating Material	Painted
Housing Material	Grey Cast Iron, Galvanised
Maximum Ambient Temperature (°C)	90
Minimum Ambient Temperature (°C)	-30

### Dimensions

Castor Diameter (mm)	25
Castor Width (mm)	6.5
Sensor Height (mm)	229
Sensor Length (mm)	64
Sensor Width (mm)	118

### Protection & Standards

Degree of Protection	IP65
Standards and Approvals	EN IEC 60947-5-1

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------