

Product No: 943 940-999-005

**HIRSCHMANN MAR1030-40 TT TT TT TT TT TT TT 99 99 99 99 99
99 U C9 HPHHXX.X. MANAGED RACKMOUNT SWITCH 943 940-
999-005**

FEATURES

- Ruggedized Managed Rackmount Switch
- Fast Ethernet with 16 x 10/100 Mbit/s RJ45 Twisted Pair ports
- 4 x Multimode 100 Mbit/s SC fiber ports
- Operating temperature range from 0 °C to +60 °C
- Dual power supply inputs: 24/36/48 V DC (spring clip)
- Layer 2 Professional network management features
- Compliant with standards cUL508, cUL1604 Class 1 Div2, Germanischer Lloyd, IEC 61850-3, IEEE 1613, EN 50121
- Designed for mounting in a standard 19" control cabinet
- IP30 protection rating

General Information

Brand	HIRSCHMANN
Series	MAR1030

Technical Attributes

No. of 100Mb Ports	12
No. of 1GB Ports	4
No. of Ethernet Ports	12
No. of Fiber Ports	4
Rated Maximum Operational Voltage DC (V)	48
Rated Minimum Operational Voltage DC (V)	24

Physical Attributes

Maximum Temperature (°C)	85
Minimum Temperature (°C)	-40
Mounting Type	19" Control Cabinet

Protection & Standards

Degree of Protection	IP30
Standards and Approvals	IEC 61850-3

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------