

## Product No: DRM2P150

### DEHN 1PH CLASS3 4KA 8/20US IN-LINE 150VAC SURGE DEHNRAIL 953204 DRM2P150

#### FEATURES

- Two-pole surge arrester consisting of a base part and a plug-in protection module.
- High discharge capacity due to heavy-duty zinc oxide varistor / spark gap combination.
- Energy coordination with other arresters of the Red/Line product family.



#### General Information

Brand	DEHN
Product Type	Surge Protection Device
Suitable For	Indoor installation only.

#### Technical Attributes

Nominal Discharge Current (8/20 $\mu$ s) - In (kA)	2
Nominal Voltage (V)	120 V (50 / 60 Hz)
Overcurrent Protection	Max. 25 A gG or B 25 A Main Side
Response Time (ns)	$\leq 25$ [L-N] , $\leq 100$ [L/N-PE]
SPD Type	type 3 / class III
Voltage Protection Level - Up (kV)	$\leq 0.64$ / $\leq 0.8$ [L-N] / [L/N-PE]

#### Physical Attributes

Operational Temperature Range (°C)	-40 °C ... +80 °C
------------------------------------	-------------------

#### Dimensions

Cable Cross Section (mm <sup>2</sup> )	Min. 0.5 mm <sup>2</sup> solid / flexible. Max. 4 mm <sup>2</sup> stranded / 2.5 mm <sup>2</sup> flexible
--	--