

Product No: IS-SL36-EC90

NOVARIS INTRINS. SAFE SURGE PROT. IS-SL36-EC90 IS-SL36-EC90

FEATURES

- - Transverse and common mode protection
- - Slimline pluggable module
- - Protection for most twisted pair signaling schemes
- - IEC Ex and ATEX certified



General Information

Brand	NOVARIS
Product Type	Signal Line Protector
Series	IS-SL

Technical Attributes

Connection Type	Series
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	1 (per line), 2 (common mode)
Maximum Continuous Operating Voltage MCOV AC (V)	24
Maximum Continuous Operating Voltage MCOV DC (V)	34
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	5 (per line), 10 (common mode)
Maximum Load Current - I _l (A)	0.25
No. of Pairs	1
Voltage Protection Level (3kA 8/20 μ s) - U _p (kV)	0.055 (L-L, L-PE)

Physical Attributes

Base Option	EC90 (Indirect Earthing)
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-20 to 40

Dimensions

Dimensions (mm)	7W x 68H x 102L
-----------------	-----------------

Protection & Standards

Degree of Protection IP20

Resources

Product catalogue (Flipbook) [Download from here](#)

TECHNICAL DRAWING

