

Product No: 101055354

SCHMERSAL MICRO SWITCH INO+INC MS 6600-11-K-Y

Note: Contact symbols shown for the closed condition of the guard device.



General Information

Brand	SCHMERSAL
Cable Note	All indications including the conductor ferrules.
Coding Level According to EN ISO 14119	Low
EAN	4030660000000
eCl@ss Number, Version 11.0	27-27-01-03
eCl@ss Number, Version 9.0	27-27-01-03
ETIM 6.0	EC000030
ETIM 7.0	EC000030
Housing Construction Form	Cylinder thread
No. of Beams	36
Product Type	Micro Switch
Protection Class of Operating Resource	3
Recommended Actuator	BPS 33-2326 BPS 33
Recommended Safety Switchgear	SRB-E 301
Version	Round Push button
Working Principle	Magnetic drive

Technical Attributes

No. of Auxiliary Contacts	1
Switchover Time (ms)	35
Actuating Torque (Nm)	0.15
Actuator Type to EN 50047	A

Assured "OFF" Switching Distance (mm)	17
Assured "ON" Switching Distance (mm)	7
Bounce Duration	Bounce duration in accordance with actuating speed
Coding Type	Individual coding, multiple teaching
Connector Type	Connector plug M12, 4-pole
Contact Material	Silver
Design of Control Element	p-type
Detection Ability for Test Bodies @ V = 1.6 m/s	30 mm
Height of The Protection Field (mm)	810
Integral System Diagnostics Status	Yes
Latching Force (N)	30
Maximum Actuating Speed (m/s)	1
Maximum Bounce Duration (ms)	2
Maximum Cable Cross Section (mm ²)	2.5
Maximum Electrical Power Consumption (W)	10
Maximum Fuse Rating	6 A gG D-fuse
Maximum Holding Force (N)	2600
Maximum Leakage Current (mA)	0.5
Maximum No-load Supply Current (mA)	600
Maximum Output Current (A)	0.25
Maximum Permissible Installation Altitude Above Sea Level (m)	2000
Maximum Protection Field (mm)	6000
Maximum Reaction Time (ms)	10
Maximum Switching Capacity (W)	5
Maximum Switching Current (A)	0.01
Maximum Switching Frequency (Hz)	5
Maximum Switching Voltage DC (V)	24
Minimum Actuating Force (N)	9
Minimum Actuating Speed (mm/min)	60
Minimum Cable Cross Section (mm ²)	0.75

Minimum Positive Break Force (N)	40
Minimum Protection Field (mm)	300
No. of Actuating Directions	2
No. of Cable Wires	4
No. of Normally-open Contacts	1
No. of Safety Contacts	3
Overtoltage Category	3
Positive Break Torque (Nm)	0.185
Positive Break Travel (mm)	3.5
Rated Control Voltage AC (V)	230
Rated Control Voltage DC (V)	24
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	500
Rated Operating Current (mA)	4000
Rated Short-circuit Current (A)	1000
Resistance to Shock (g/ms)	30 / 11
Switching Element	Opener (NC)
Switching Principle	Slow action
Switchover Time	Switchover time in accordance with actuating speed
Terminal Type	Screw terminals M20 x 1.5
Tolerance	10%
Utilisation Category	DC-13 AC-15
Utilisation Category AC-15	230 VAC
Utilisation Category DC-13	2.5 A, 24 VDC
Voltage Type	DC
Wavelength of The Sensor (nm)	880

Physical Attributes

Active Area	Plastic
Actuator Type	Roller plunger

Cable Entry	3 x M16 x 1.5
Colour of The Front Ring	Silver
Design	Round
Direction of Motion	Head-on to the active surface
Enclosure Coating Material	Nickel-plated
Enclosure Material	Stainless steel
Front Ring Material	Aluminium
Gross Weight (g)	29.331
Installation Conditions	Quasi-flush
Lever Material	Metal film
Material of The Cable Mantle	PVC
Material of The Operators	Glass
Maximum Ambient Temperature (°C)	80
Maximum Relative Humidity	95%
Minimum Ambient Temperature (°C)	-25
Minimum Relative Humidity	30%
Mounting Type	Central with threaded flange M12 x 1
Net Weight (g)	50
Recipient Terminal Connector Type	Connector plug M12, 5-pole
Roller Material	Plastic
Sealing Type	Form seals / Lip gaskets / Membrane
Storage Temperature (°C)	-25 to 70
Wire Cross-Section	23 AWG

Dimensions

Cable Length (m)	1
Castor Diameter (mm)	20
Depth (mm)	60
Height (mm)	103
Sensor Height (mm)	90
Sensor Length (mm)	13

Spacing (mm)	40 x 50
--------------	---------

Width (mm)	10
------------	----

Protection & Standards

Degree of Protection	IP67
----------------------	------

Explosion Protection Category	3D 3G
-------------------------------	---------

Explosion Protection Zones	22 2
----------------------------	--------

Pollution Degree	3
------------------	---

Standards	EN IEC 60947-5-1 / EN IEC 60947-1
-----------	-----------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------