


Product No: 942 170-048

HIRSHMANN MANAGED INDUSTRIAL SWITCH FOR DIN RAIL 4X GIG SFP, 8X FAST ETHERNET TX, 48/54 V DC, 0 - +60°C, HIOS L2S, POE+ 942170048

FEATURES

- Store and Forward Switching Mode
- Fanless design
- Ethernet/Fast-Ethernet Switch



General Information

Brand	HIRSHMANN
Product Type	Managed
Reference No.	BRS32-08040000-SPCY99HHSESXX.X
Series	BOBCAT

Technical Attributes

Electromagnetic Capability	10 V/m (80-2000 MHz) 5 V/m (2000-2700 MHz) 3 V/m (5100-6000 MHz)
Electrostatic Discharge (kV)	6 kV Contact Discharge, 8 kV Air Discharge
Port Quantity and Type	8 x FE + 4 x GE, 2 x SFP Slot (Uplink 1), 2 x SFP Slot (Uplink 2)
Rated Operational Voltage DC (V)	2 x (48 (PoE) / 54 (PoE+))
Resistance to Vibrations	5 Hz ... 8,4 Hz with 3,5 mm amplitude 2 Hz ... 13,2 Hz with 1 mm amplitude 8,4 Hz ... 200 Hz with 1 g 13,2 Hz ... 100 Hz with 0,7 g
Surge Voltage (kV)	Power Line: 2 kV (Line/Earth) and 1 kV (Line/Line); Data Line: 2 kV
Transition Type	2 kV Power Line, 2 kV Data Line

Physical Attributes

Mounting Type	DIN Rail
Operational Temperature Range (°C)	0 to +60

Dimensions

Cable Length (m)	0 - 100
------------------	---------

Protection & Standards

Degree of Protection	IP30 (Housing)
----------------------	----------------

Standards and Approvals	CE, FCC, EN61131, EN62368-1, cUL61010
-------------------------	---------------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------