

## Product No: MCB-20

### ABB CONTACT BLOCK 2NO FRONT MOUNT MCB-20



#### General Information

Accessory Type	Contact Block
Brand	ABB
Product Type	Accessory
Suitable For	Pilot Devices

#### Technical Attributes

Connecting Capacity	Flexible with Ferrule 1/2 x 0.75 - 2.5mm <sup>2</sup> Flexible with Insulated Ferrule 1/2 x 0.75 - 2.5mm <sup>2</sup> Flexible 1/2 x 0.75 - 2.5mm <sup>2</sup> Solid 1/2 x 0.75 - 2.5mm <sup>2</sup>
Connection Type	Screw Clamp
Illumination	Non-illuminated
No. of Normally-open Contacts	2
Power Loss (W)	5
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	690
Rated Operational Current AC-15 230V (A)	6
Rated Operational Current DC-13 125V (A)	0.55
Rated Operational Current DC-13 24V (A)	5
Rated Operational Voltage (V)	690 (Maximum)
Rated Operational Voltage AC/DC (V)	690
Terminal Type	Screw

Tightening Torque (Nm)	0.9
------------------------	-----

Wire Stripping Length (mm)	8
----------------------------	---

### Physical Attributes

Ambient Temperature Range (°C)	-25 to 70
--------------------------------	-----------

Mounting Type	Front Mount
---------------	-------------

Storage Temperature Range (°C)	-40 to 85
--------------------------------	-----------

### Dimensions

Dimensions (mm)	20W x 44H x 28D
-----------------	-----------------

Weight (kg)	0.04
-------------	------

### Protection & Standards

Degree of Protection	Terminals: IP20
----------------------	-----------------

Pollution Degree	3
------------------	---

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------