

Product No: UF40.241

PULS BUFFER MODULE 24VDC 40A UF40.241

FEATURES

- Buffering with electrolytic capacitors instead of lead acid batteries
- Buffering of 24V loads
- Minimum hold-up time 0.16s at 40A, 0.2s, longer hold-up time at lower loads
- Clear status indication by status LED and signaling terminals
- Quick-connect spring-clamp terminals



General Information

Brand	PULS
Country of Origin	China / Czech Republic
Customs Tariff Number	85044083
E Classification	E-CS04
Product Type	Buffer Module
Range	DIMENSION
Series	U series
Warranty Period (Months)	36

Technical Attributes

Connection Type	Screw terminals
Efficiency	%
Input Voltage Range DC (V)	24
Minimum Input Voltage DC (V)	24
Nominal Output Current 'b' (A)	40
Output Voltage (V)	24
Rated Current (A)	40
Storage Element	Electrolytic capacitors
Use In Crosslinking	Yes

Physical Attributes

Conformal Coating	No
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-25 to 70

Dimensions

Dimensions (mm)	64W x 124H x 142D
Weight (g)	1040

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	EU Declaration of Conformity, IEC 60950 CB Scheme, IEC 61010-2-201 CB Scheme, Korea Certification, UL 60950-1 Canada, UL 60950-1 USA, UL 61010-2-201 Canada, UL 61010-2-201 USA, UK Declaration of Conformity

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------