

Product No: RR3PA-ULAC240

IDEC RELAY, 3PDT, 240V AC, 10A WITH INDICATOR OR ROUND 11 PIN RELAY RR3PA-ULAC240

FEATURES

- High reliability and long service life
- Worldwide approvals on octal (8-pin and 11-pin) models: UL, CSA, TUV, CE
- Options include check button for test operation and indicator light
- Mounting options include flange mounting, DIN socket, or panel mount socket

General Information

Brand	IDEC
Model	With Indicator
Product Type	Power

Technical Attributes

Coil Voltage AC (V)	240
Contact Material	Silver
Contacts	3PDT
Insulation Resistance (MΩ)	100
Minimum Electrical Life	200,000
Minimum Mechanical Life	10,000,000
Operating Time	25ms
Resistance to Shock (m/s ²)	100
Resistance to Vibrations	10 to 55Hz

Physical Attributes

Operating Humidity	5 to 85%
Operational Temperature Range (°C)	-25 to 40
Terminal Shape	Pin Terminal

Dimensions

Dimensions (mm)	35.6W x 68.5H x 35.6D
-----------------	-----------------------

Weight (g)	96
------------	----

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------