


Product No: OT160EV03P

ABB OT160EV03P SWITCH-DISCONNECTOR OT160EV03P

FEATURES

- Front operated, 3 pole switch disconnecter
- Mechanism is at left end of the switch
- Base mounted
- With black handle and shaft
- Terminal bolt kit included
- Degree of protection: Handle IP65/ Front IP00



General Information

Brand	ABB
Included	Handle, Shaft
Product Type	Base Mount Load Break Switch
Type	Main Switch

Technical Attributes

Conventional Free-Air Thermal Current - I _{th} (A)	200
Conventional Thermal Current - I _{the} (A)	160
Main Circuit Electrical Connection	Bolt Connection
Maximum Operational Voltage AC (V)	1000
Mode of Operation	Front operated
No. of Poles	3
Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)
Power Loss (W)	3.2/Pole
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage (V)	1000
Rated Operational Current AC-21A 415V (A)	200
Rated Operational Current AC-22A 380-415V (A)	200
Rated Operational Current AC-22A 500V (A)	200
Rated Operational Current AC-22A 690V (A)	160
Rated Operational Current AC-23A 380-415V (A)	160

Rated Operational Current AC-23A 690V (A)	160
Rated Operational Power AC-23A 380-415V (kW)	88
Rated Operational Power AC-23A 400-415 V (kW)	88
Rated Operational Power AC-23A 500V (kW)	112
Rated Operational Power AC-23A 690V (kW)	144
Rated Operational Voltage (V)	1000
Rated Short-Time Withstand Current - I _{cw} (kA)	8
Rated Short-time Withstand Current - I _{cw} (kA/1s)	8
Rated Uninterrupted Current - I _u (A)	160
Terminal Type	Lug terminals

Physical Attributes

Control Element Colour	Black
Handle Colour	Black
Handle Dimensions (mm)	98W x 45H x 66D
Handle Material	Plastic
Handle Type	Pistol
Interlockable	Yes
Mounting Type	Base Mount
Shaft Dimensions (mm)	6W x 6H x 210D

Dimensions

Cable Cross Section (mm ²)	70
Dimensions (mm)	150W x 145.5H x 82.5D
Handle Length (mm)	65

Protection & Standards

Degree of Protection - Handle	IP65
Pollution Degree	3
Standards and Approvals	IEC 60947-3

Resources



Product catalogue (Flipbook)

[Download from here](#)
