

CA713/2



connectwell
THE RIGHT CONNECTION

External Comb Type Shorting Link

External shorting links bridge potentials between terminal blocks, reducing wiring time. Adjacent or selected blocks within an assembly can be easily interconnected. Individual links may be removed for selective shorting. These are insulated and available in 2, 3, 4 and 10 pole versions. They are made of tin plated brass/copper. Comb Link must be tightened to the recommended torque specified to get a reliable connection.

PRODUCT SPECIFICATION

| | |
|---------------|--------|
| Rated Current | 24 A |
| Torque | 0.4 Nm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|----------|---|-----------|
| CA713/2 | External Comb Type Shorting Link available in 2 Pole | 100 |
| CA713/3 | External Comb Type Shorting Link available in 3 Pole | 100 |
| CA713/4 | External Comb Type Shorting Link available in 4 Pole | 100 |
| CA713/10 | External Comb Type Shorting Link available in 10 Pole | 20 |

SUITABLE FOR

| | |
|-------------|---|
| CMC2-2 | 4 sq.mm Multiple Connection Terminal Blocks with 4 connection points. |
| CTS4UN | 4 sq.mm Standard Feed Through Terminal Blocks |
| CTS2.5UE EX | 2.5 sq.mm, 6 mm thick Feed Through Terminal Block |
| CTS4UNP | 4 sq.mm Feed Through Philips Head screw Terminal Blocks |
| CDS4U | 4 sq.mm Disconnect & Test Terminal Blocks |
| CTS4UNV0 | 4 sq.mm Feed Through Terminal Blocks |
| CDT4 | 4 sq.mm Disconnect & Test Terminal Blocks |
| CTS2.5UE | 2.5 sq.mm, 6 mm thick Feed Through Terminal Block |
| CTS4UNCR | 4 sq.mm Feed Through Terminal Blocks |