

## ABB S202MC13 MCB 10kA 2P 13A 400VAC C CURVE INDUSTRIAL

S202MC13

### FEATURES

- Protection against short circuit and thermal overload
- Twin terminal for separate feeding of busbar and conductor
- Contact Position Indication
- Captive screws
- Finger safety with IP20 terminals
- Pole configuration 2P



### GENERAL INFORMATION

|              |       |
|--------------|-------|
| Brand        | ABB   |
| Product Type | MCB   |
| Series       | S200M |

### TECHNICAL ATTRIBUTES

|  |                           |
|--|---------------------------|
| Application  | Commercial and Industrial |
| Breaking Capacity 400V AC - Icu (kA)               | 15                        |
| Curve Type   | C Curve                   |
| Maximum Operational Voltage AC (V)                 | 440                       |
| Maximum Operational Voltage DC (V)                 | 125                       |
| Minimum Operational Voltage AC (V)                 | 12                        |
| Minimum Operational Voltage DC (V)                 | 12                        |
| No. of Poles                                       | 2P                        |
| Power Loss (W)                                     | 2.3/Pole                  |
| Rated Conditional Short-Circuit Current - Inc (kA) | 25                        |
| Rated Current (A)                                  | 13                        |
| Rated Frequency (Hz)                               | 50/60                     |
| Rated Impulse Withstand Voltage (kV)               | 4                         |
| Rated Insulation Voltage (V)                       | 440                       |
| Rated Operational Voltage AC (V)                   | 400                       |
| Rated Short-Circuit Capacity - Icn (kA)            | 10                        |
| Rated Voltage AC (V)                               | 400                       |

**PHYSICAL ATTRIBUTES**

|                  |                               |
|------------------|-------------------------------|
| Housing Material | Insulation Group II, RAL 7035 |
| Mounting Type    | DIN Rail                      |

**DIMENSIONS**

|   |                    |
|---|--------------------|
| Busbar Cross Section (mm <sup>2</sup> )                 | Top/Bottom - 10/10 |
| Cable Cross Section - Flexible (mm <sup>2</sup> )       | Top/Bottom - 25/25 |
| Cable Cross Section - Solid/Stranded (mm <sup>2</sup> ) | Top/Bottom - 35/35 |
| Dimensions (mm)   | 85H x 69D x 35W    |
| Pole Width (mm)   | 17.5               |

**PROTECTION & STANDARDS**

|                         |                                       |
|-------------------------|---------------------------------------|
| Degree of Protection    | IP20                                  |
| Pollution Degree        | 3                                     |
| Standards and Approvals | AS/NZS 60898-1,AS/NZS 60947-2,UL 1077 |