

Product No: 942 084-999-006

HIRSCHMANN MANAGED DIN RAIL SWITCH RSPE30-2404407T99ECCZ999HHSE2S 942 084-999-006

FEATURES

- Managed Switch with Enhanced Redundancy (HSR, PRP, Fast MRP)
- Up to 28 ports: 24 Fast Ethernet and 4 Gigabit Ethernet
- Supports twisted pair cable and fiber optic connections (via SFP)
- Power input options: 60 to 250 V DC and 110 to 230 V AC
- Operating temperature range from 0 °C to +60 °C
- HiOS Layer 2 Standard software
- Compliant with CE, FCC, EU Safety standards
- Designed for substation environments (IEC 61850-3 certified)
- IP30 rated enclosure for protection against objects greater than 2.5mm

General Information

Brand	HIRSCHMANN
Series	RSP

Technical Attributes

No. of 100Mb Ports	24
No. of 1GB Ports	4
No. of Ethernet Ports	12
No. of Fiber Ports	16
Nominal Power (W)	16
Rated Maximum Operational Voltage DC (V)	60
Rated Minimum Operational Voltage DC (V)	24

Physical Attributes

Maximum Temperature (°C)	70
Minimum Temperature (°C)	-40

Protection & Standards

Degree of Protection

IP30

Resources

Product catalogue (Flipbook)

[Download from here](#)