

Product No: DGM TT2P320FM

DEHN SPD 2P CLASS 2 40KA 8/20US2C+EA 320VAC +CO GUARD DGM TT2P320FM

FEATURES

- Multipole DEHNguard M surge arrester
- Consisting of a base part and plug-in protection modules
- High reliability due to "Thermo Dynamic Control" SPD monitoring device
- For protecting low-voltage consumer's installations against surges
- For installation in conformity with the lightning protection zone concept at the boundaries from OB "1 and higher



General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	952135
Suitable For	Power Supply Systems

Technical Attributes

Breaking Capacity AC (kA)	25
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	12
Maximum Continuous Voltage AC (V)	320
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	40
No. of Conductors	2
Nominal Discharge Current (8/20 μ s) - I _n (kA)	20
Nominal Voltage AC (V)	230

Dimensions

Dimensions (mm)	36W x 90H x 66D
Weight (kg)	0.253

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	EN 61643-11

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------