

Product No: DVMTT255FM

DEHN 4P NON-MEN CLASS1 25kA10/350US 255VAC +CO VENTIL DVMTT255FM

FEATURES

- Multipole DEHNventil modular type 1 and type 2 spark-gap-based combined lightning current and surge arrester
- Consisting of a base part and pluggable protection modules
- Maximum availability due to RADAX Flow follow current limitation
- Capable of protecting terminal equipment
- For protecting low-voltage consumer's installations against surges and even direct lightning strikes
- For installation in conformity with the lightning protection zone concept at the boundaries from 0A " 2



General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	951315
Suitable For	Power Supply Systems

Technical Attributes

Follow Current Extinguishing Capability AC (kArms)	50
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	100
Maximum Continuous Voltage AC (V)	264
No. of Poles	4
Nominal Voltage AC (V)	230

Physical Attributes

Enclosure Material	Thermoplastic
--------------------	---------------

Dimensions

Dimensions (mm)	73W x 90H x 144D
-----------------	------------------

Weight (kg)	1.32
-------------	------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Standards and Approvals	EN 61643-11
-------------------------	-------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------