

## Product No: F202A40/0.03

### ABB F202A40/0.03 RCCB 10kA 1P+N 40A TYPE A 30mA INDUSTRIAL

#### FEATURES

- - Protection for people and buildings against earth leakage faults
- - Used where earth fault waveform may be sinusoidal or pulsating DC
- - Test button for checking the correct function of the device
- - Bidirectional cylindrical clamps assist and increase safety during connecting procedures
- - Contact Position Indication (CPI)
- - Laser printed data for quick identification
- - Pole configuration 1P+N



#### General Information

Brand	ABB
Product Type	RCCB
Series	F200

#### Technical Attributes

Application	Commercial and Industrial
No. of Poles	2P
Power Loss (W)	2.4/pole
Rated Conditional Short-Circuit Current - Inc (kA)	10
Rated Current (A)	40
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	230
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - Icn (kA)	10
Rated Voltage AC (V)	230/400
Type of Residual Current	A

### Physical Attributes

Mounting Type	DIN Rail
---------------	----------

---

### Protection & Standards

Degree of Protection	IP20
----------------------	------

---

Pollution Degree	2
------------------	---

---

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------

---