

Product No: MS116-32

ABB MS116-32 MANUAL MOTOR STARTER 25 ... 32 A MS116-32

FEATURES

- Compact design, ideal for installations with limited space
- Provides reliable protection against short-circuits, overload and phase failures
- High breaking capacity
- Features a lockable rotary handle with clear switch position indication
- Suitable for both 3 phase and single phase applications



General Information

Brand	ABB
Product Type	Manual Motor Starter

Technical Attributes

Design of Control Element	Turn Button
Breaking Capacity 400V AC - I _{cu} (kA)	16
Main Circuit Electrical Connection	Screw Connection
No. of Poles	3
Overload Release Current Setting (A)	25
Phase Failure Sensitive	Yes
Power Loss (W)	9.3
Rated Instantaneous Short-Circuit Current - I _i (A)	480
Rated Insulation Voltage (V)	690
Rated Operational Current (A)	10
Rated Operational Power AC-3 400V (kW)	15
Rated Operational Voltage (V)	690
Rated Uninterrupted Current - I _u (A)	32
Switching Type	Thermomagnetic
Terminal Type	Screw Terminals
Thermal Current Setting Range (A)	25.0 - 32.0

Thermal Overload Protection Yes

Dimensions

Dimensions (mm) 45W x 97.8H x 85.4D

Protection & Standards

Degree of Protection IP20

Resources

Product catalogue (Flipbook) [Download from here](#)
