

Product No: DS201C16A10

ABB DS201C16A10 RCBO 6kA 1P+N 16A C CURVE TYPE A 10mA

FEATURES

- - Protection against short circuit, thermal overload and earth leakage
- - Contact Position Indication (CPI)
- - Earth fault indicator to identify easier earth faults
- - Test pushbutton to verify the correct functioning of the device
- - Laser printed data for quick identification
- - Finger safety with IP20 terminals
- - Pole configuration 1P+N



General Information

Brand	ABB
Product Type	RCBO
Series	DS201

Technical Attributes

Application	Commercial and Industrial
Breaking Capacity 230V AC - I _{cu} (kA)	10
Curve Type	C Curve
No. of Poles	1P+N
Power Loss (W)	3.3
Rated Conditional Short-Circuit Current - I _{nc} (kA)	10
Rated Current (A)	16
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	230/240
Rated Residual Current (mA)	10
Rated Short-Circuit Capacity - I _{cn} (kA)	6
Rated Voltage AC (V)	230
Test Voltage (kV)	0.11-0.264

Type of Residual Current	A
--------------------------	---

Physical Attributes

Housing Material	Insulation Group I – II, RAL 7035
------------------	-----------------------------------

Mounting Type	DIN Rail
---------------	----------

Protection & Standards

Degree of Protection	IP40 (Housing), IP20 (Terminals)
----------------------	----------------------------------

Pollution Degree	2
------------------	---

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
