

Product No: ISDA077658R1

ABB E2.2S-A 1600 EKIP DIP LI 3P WMP ISDA077658R1

FEATURES

- IP30 protection for fixed parts
- Lifting plates
- Adjustable rear terminals
- Racked-out mechanism lock, anti-insertion lock, standard shutter lock
- Lever for racking in/out
- AUX 4Q 400V Open-Closed changeover contact
- TU Reset push button
- S51 250V trip indicator



General Information

Brand	ABB
Product Type	Automatic ACB

Technical Attributes

Design of Control Element	Push Button
Indication	Switched-off Indicator
Main Circuit Electrical Connection	Connection at Separate Chassis Part
Main Current Circuit Connection Position	Connection at Separate Chassis Part
No. of Auxiliary Change-over Contacts	4
No. of Poles	3
Overload Release Current Setting (A)	640
Power Loss (W)	260
Rated Current (A)	1600
Rated Instantaneous Short-Circuit Current - I _i (A)	2400
Rated Insulation Voltage AC (V)	635
Rated Operational Voltage AC (V)	600
Rated Uninterrupted Current - I _u (A)	1600
Rated Voltage (V)	600
Trip Unit	Ekip Dip LI

Dimensions

Size of Frame	E2.2
---------------	------

Protection & Standards

Degree of Protection	IP30
----------------------	------

Standards and Approvals	UL
-------------------------	----