

Product No: DRL10B180FSD

DEHN DEHNRAPID LIGHT N. CURR. ARR. LSA F. 10 PAIRS, FAIL-SAFE FUNCT., FAULT INDICATOR DRL10B180FSD

FEATURES

- Lightning current arrester plug-in block
- SPD class TYPE 1
- Tested to EN 61643-21
- Extendible to a combined lightning current
- Surge arrester with DRL protective plug
- With fail-safe function and visual fault indicator



General Information

Article No.	907401
Brand	DEHN
Product Type	Signal Line Protector

Technical Attributes

Lightning Impulse Current (10/350 μ s) - Iimp (kA)	2.5 (Per Line)
Maximum Continuous Operating Voltage MCOV AC (V)	127
Maximum Continuous Operating Voltage MCOV DC (V)	180
Nominal Discharge Current (8/20 μ s) - In (kA)	5 (Per Line)
Nominal Voltage (V)	180
Total Discharge Current (10/350 μ s) - Itotal (kA)	5
Total Discharge Current (8/20 μ s) - Itotal (kA)	10
Voltage Protection Level - Up (kV)	≤ 0.5 (Line-Line)/ ≤ 0.5 (Line-PG)

Physical Attributes

Pluggable	Plugs in to LSA disconnection block 2/10
-----------	--

Dimensions

Dimensions (mm)	0.04W x 0.17L x 0.04D
Weight (kg)	0.07

Protection & Standards

Degree of Protection

IP10

Resources

Product catalogue (Flipbook)

[Download from here](#)