

## ABB AF65302213 AF CONTACTOR 3P 105A (AC-1), 30KW 400VAC, CONTROL 100-250 VAC/DC AUX 2NO+2NC

AF65302213



### GENERAL INFORMATION

|              |              |
|--------------|--------------|
| Brand        | ABB          |
| Product Type | AF Contactor |

### TECHNICAL ATTRIBUTES

|   |                     |
|---|---------------------|
| Auxiliary Contacts                      | 2NO/2NC             |
| Contacts                                | 3NO (Main Contacts) |
| No. of Poles                            | 3P                  |
| Rated Control Circuit Voltage AC/DC (V) | 100 - 250           |
| Rated Frequency (Hz)                    | 50/60               |
| Rated Impulse Withstand Voltage (kV)    | 6                   |
| Rated Insulation Voltage (V)            | 690                 |
| Rated Operational Current AC-1 690V (A) | 105                 |
| Rated Operational Current AC-3 415V (A) | 65                  |
| Rated Operational Power AC-3 415V (kW)  | 37                  |
| Rated Operational Voltage AC (V)        | 690                 |
| Terminal Type                           | Screw               |

### PHYSICAL ATTRIBUTES

|               |                |
|---------------|----------------|
| Mounting Type | DIN Rail/Panel |
|---------------|----------------|

### DIMENSIONS

|                 |                     |
|-----------------|---------------------|
| Dimensions (mm) | 125.5H x 144D x 55W |
|-----------------|---------------------|

## PROTECTION & STANDARDS

Degree of Protection

IP10 (Main Terminals), IP20 (Coil/Aux. Terminals)

---