

Product No: 942 307-003

HIRSCHMANN UNMANAGED, 8X 10/100 BASE TX / RJ45 WITH POE, 55W POWER BUDGET ,AC HV 942307003

FEATURES

- Unmanaged Ethernet Switch Range for Building Automation Applications
- MDRC form factor
- No signal contact



General Information

Brand	HIRSCHMANN
Product Type	Unmanaged

Technical Attributes

Electrostatic Discharge (kV)	4 kV Contact Discharge, 8 kV Air Discharge
Operating Voltage Range	100 - 240 V AC
Power Consumption (W)	Expected Max 12 (Without Media Modules)
Power Output in BTU (IT)/h	8.6 (Without PoE) / 37.6 (With 55 W PoE Load)
Resistance to Vibrations	3.5 mm, 5-8.4 Hz, 10 cycles, 1 octave/min 1 g, 8.4-150 Hz, 10 cycles, 1 octave/min
Surge Voltage (kV)	Power Line: 2 kV (Line/Earth), 1 kV (Line/Line); Data Line: 1 kV
Transition Type	2 kV Power Line, 2 kV Data Line

Physical Attributes

Mounting Type	DIN Rail
Operational Temperature Range (°C)	-5 - 60
Relative Humidity	20-90 %
Storage Temperature Range (°C)	-40 - 85

Dimensions

Dimensions (mm)	210W x 90H x 64D
Weight (g)	410

Protection & Standards

Standards

CE;FCC

Resources

Product catalogue (Flipbook)

[Download from here](#)
