

Product No: OT25F3C

ABB OT25F3C CHANGE-OVER SWITCH OT25F3C

FEATURES

- Modular design, the handle and shaft can be ordered separately
- Easy front operation, enhancing accessibility and ease of use
- Open transition ensures a secure and reliable change-over process
- Versatile terminal positioning, providing flexibility in installation



General Information

Brand	ABB
Included	Knob Handle
Product Type	Manual
Suitable For	Distribution Board Installation
Type	Main Switch

Technical Attributes

Conventional Free-Air Thermal Current - I _{th} (A)	25
Indication	I-O-II
Maximum Operational Voltage AC (V)	750
Mode of Operation	Front
No. of Poles	3
No. of Switches	1
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss (W)	0.6
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	750
Rated Operational Current AC-21A 415V (A)	25
Rated Operational Current AC-22A 415V (A)	25
Rated Operational Current AC-23A 380-415V (A)	20

Rated Operational Power AC-23A 380-415V (kW)	9
Rated Operational Power AC-23A 415V (kW)	9
Rated Operational Voltage (V)	750
Rated Operational Voltage AC (V)	415
Rated Short-Time Withstand Current - I _{cw} (kA)	0.5
Terminal Type	Screw
Transition Type	Open

Physical Attributes

Control Element Colour	Black
Interlockable	Yes
Mounting Type	Front Mount 4-hole

Dimensions

Cable Cross Section (mm ²)	0.75 - 10
Dimensions (mm)	55W x 68H x 68D
Weight (kg)	0.25

Protection & Standards

Degree of Protection	IP20
NEMA Degree of Protection	1
Pollution Degree	3

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------