

## Product No: CRM024AC4L

### ABB RELAY PLUGGABLE INTERFACE 24V AC 4C/O 6A CRM024AC4L

#### FEATURES

- Compact design for limited space
- Easily mounts on DIN Rail
- Switches multiple circuits with single input
- Integrated test button for manual actuation
- LED indicator for quick status check



#### General Information

Brand	ABB
Product Type	Interface Relay
Reference No.	CR-M024AC4L

#### Technical Attributes

Function	Pluggable Miniature Interface Relay CR-M
Output Signal	250V/6A
Outputs	4 x Change-over (SPDT) Contacts
Rated Control Supply Voltage AC (V)	24
Rated Frequency (Hz)	50/60
Rated Insulation Voltage (V)	250
Rated Operational Current AC-12 230V (A)	6
Rated Operational Current AC-15 120V (A)	1.5
Rated Operational Current AC-15 230V (A)	1
Rated Operational Current DC-12 24V (A)	6
Rated Operational Current DC-13 24V (A)	2
Rated Operational Current DC-13 250V (A)	0.1
Rated Operational Voltage (V)	250
Sub-Function	Relay with Built-in LED
Terminal Type	Flat-pin Connections

### Physical Attributes

Ambient Temperature Range (°C)	-40 to 55
--------------------------------	-----------

Storage Temperature Range (°C)	-40 to 85
--------------------------------	-----------

### Dimensions

Dimensions (mm)	21.2W x 35.6H x 27.5D
-----------------	-----------------------

Weight (kg)	0.033
-------------	-------

### Protection & Standards

Degree of Protection	IP40
----------------------	------

Standards and Approvals	IEC/EN 63000, IEC/EN 61810-1, UL 508
-------------------------	--------------------------------------

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------