


Product No: IS-SLT3-36-M20

NOVARIS IS-SLT INTRINSICALLY SAFE SURGE PROTECTOR IS-SLT3-36-M20

FEATURES

- - Transverse & common mode protection
- - Thread size M20 x 1.5
- - GDT and MOV protection stages
- - 0.75mm² flying leads



General Information

Brand	NOVARIS
Product Type	Signal Line Protector
Series	IS-SLT

Technical Attributes

Connection Type	Shunt
Maximum Continuous Operating Voltage MCOV AC (V)	30
Maximum Continuous Operating Voltage MCOV DC (V)	36
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	5 (per line), 10 (common mode)
No. of Lines	3
Thread Size	M20 x 1.5
Voltage Protection Level (1kV/ μ s) - U _p (kV)	0.075 (L-L), 0.35 (L-PE)

Physical Attributes

Operational Temperature Range (°C)	-20 to 40
------------------------------------	-----------

Dimensions

Dimensions (mm)	24W x 27H x 53L
Weight (g)	145

Protection & Standards

Degree of Protection	IP67
----------------------	------

21, AS/NZS 1768, UL 1449

Resources

Product catalogue (Flipbook)

[Download from here](#)

TECHNICAL DRAWING

