

Product No: ESB2513N14

ABB ESB25-13N-14 INSTALLATION CONTACTOR (NC) 25 A - 1 NO - 3 NC - 12 V - CONTROL CIRCUIT 400 HZ ESB2513N14

FEATURES

- Operates seamlessly with both AC and DC power sources
- Quiet and efficient operation
- Integrated overvoltage protection
- Customisable configuration



General Information

Brand	ABB
Product Type	DIN Contactor

Technical Attributes

Contacts	1NO, 3NC
Excitation Voltage Type	AC/DC
Hum-free	Yes
No. of Normally-closed Contacts	3
No. of Normally-open Contacts	1
No. of Poles	4
Operating Voltage Type	AC/DC
Rated Control Circuit Voltage (V)	12
Rated Control Circuit Voltage AC/DC (V)	12
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	500
Rated Operational Current (A)	25
Rated Operational Current AC-1 (A)	25
Rated Operational Voltage AC (V)	400
Rated Operational Voltage DC (V)	220
Terminal Type	Screw Terminals
Utilization Category	AC-1 According to EN IEC 60947-4-1

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Physical Attributes

Width in Number of Modular Spacings	2
-------------------------------------	---

Dimensions

Built-in Depth (mm)	58
Dimensions (mm)	36W X 85H X 65D

Protection & Standards

Degree of Protection	IP20
Pollution Degree	3
Standards and Approvals	IEC/EN 60947-1, IEC/EN 60947-4-1, IEC/EN 61095