

Product No: 768D2431321142008000

BD SENSORS LMK458 PROBE FOR MARINE AND OFFSHORE LMK458 PROBE FOR MARINE AND OF 768D2431321142008000

FEATURES

- Diameter 39.5 mm.
- High overpressure resistance.
- High long-term stability.
- LR, DNV, ABS & CCS certified.



General Information

Brand	BD SENSORS
Product Series	LMK 458
Product Type	Ceramic Sensor
Version	Standard

Technical Attributes

Accuracy	0.25 % FSO
Application	Drinking water abstraction. Desalinization plant. Shipbuilding / Offshore ballast tanks. Monitoring of a ship's position and draught. Level measurement in ballast and storage tanks.
Electrical Connection	TPE-U-cable (blue, Ø 7.4 mm) [Shielded cable with integrated ventilation tube for atmospheric reference]
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326 & DNV (Det Norske Veritas).
Input Pressure (bar)	0.8...2.4
Mechanical Stability	4 g (according to DNV: class B, curve 2 / basis: DIN EN 60068-2-6)
Output Signal	4 ... 20 mA / 2-wire
Permissible Temperatures	Medium / Electronics / Environment: -25 ... 125 °C, Storage: -40 ... 125 °C

Max. response time: 380

Seals	FKM
-------	-----

Physical Attributes

Design	Flange Version [Mounting accessories are not part of supply and have to be ordered separately]
--------	--

Diaphragm Material	Ceramics Al2O3 96 %
--------------------	---------------------

Housing Material	Stainless steel 1.4404 (316L)
------------------	-------------------------------

Dimensions

Cable Length (m)	8
------------------	---

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------