

## Product No: 942 132-019

**HIRSHMANN SPIDER III STANDARD LINE, 4X 10/100 BASE TX, RJ45 & 1X 100 BASE FX MULTIMODE ST, 12-24 VDC 942132019**

### FEATURES

- Fanless design
- Store and forward switching mode
- Fast Ethernet



### General Information

Brand	HIRSHMANN
Product Type	Unmanaged
Series	SPIDER III

### Technical Attributes

Connector Type	FX Port - ST
Current Consumption (mA)	100 at 24VDC
No. of 100Mb Ports	5
No. of Ethernet Ports	4
No. of Fiber Ports	1
No. of Ports	4 x 10/100BASE-TX RJ45, 1 x 100BASE-FX
Nominal Power (W)	2.4
Power Consumption (W)	2.4
Rated Maximum Operational Voltage DC (V)	32
Rated Minimum Operational Voltage DC (V)	9.6
Rated Operational Voltage DC (V)	12 - 24
Switch Type	Switch - Unmanaged

### Physical Attributes

Cable Type	FX Cable - Multi Mode
Maximum Temperature (°C)	70
Minimum Temperature (°C)	-40

Mounting Type	DIN Rail / Wall
---------------	-----------------

Operational Temperature Range (°C)	-40 to +70
------------------------------------	------------

### Dimensions

Dimensions (mm)	102H x 26W x 79D
-----------------	------------------

### Protection & Standards

Degree of Protection	IP30
----------------------	------

Standards and Approvals	CE, FCC, EN61131, cUL61010-1/61010-2-201
-------------------------	--

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------