



Product No: **UPS403HH33B035**

**DELTA HPH THREE PHASE 40 KVA/40 KW GEN 2 MONOBLOCK  
80 X 12V 9AH WITH BATTERY UPS403HH33B035**

FEATURES

- Delta HPH 40KVA/40KW Gen 2 Monoblock
- Internal Batteries,
- 80 x 12V 9Ah Batteries included
- SMART Slot x 1, MINI Slot x 1
- 490W x 830D x 1400H (mm) – 385kg

General Information	
Brand	DELTA
Product Type	Accessory
Series	HPH
Technical Attributes	
Battery Charge Current (A)	15 (Max inbuilt)
Battery Charge Voltage DC (V)	±272 (adjustable from 204 V to 312 V)
Battery Nominal Voltage DC (V)	±240 (default, ±180 ±276 configurable)
Communication Interface	External battery temperature detection x1, Output dry contact x4, Input dry contact x2, Parallel port x2, USB Port x1, RS232 Port x1, REPO Port x1, Mini Slot x2
Input Frequency Range (Hz)	40-70
Noise Level (dBA)	< 56
Nominal Voltage AC (V)	220/380, 230/400, 240/415
Output Voltage AC (V)	220/380, 230/400, 240/415 (3-phase, 4-wire + G)
Voltage Range AC (V)	305-478 (full load), 228-478 (70% load)
Physical Attributes	
Humidity	0-95% (non-condensing)
Operational Temperature Range (°C)	0-40°
Power Rating (W)	40kVA



Dimensions

Dimensions (mm)	240 W x 630 D x 650 H
Weight (kg)	50

Protection & Standards

Degree of Protection	IP20 (Standard), IP42 (Optional for long backup model)
----------------------	--

Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------