

Product No: VS308U

ELKO POWER RELAY MODULE 3 C/O 8A, AC/DC 12-240V, 50-60Hz (UNI) RED LED VS308U

FEATURES

- Handles AC 0.7 - 3 VA and DC 0.5 - 1.7 W
- Three changeover contacts: each capable of 8A (AgNi/Silver Alloy)
- DIN Rail mounting, compatible with DIN Rail EN60715 for easy installation
- IP40/IP20 Protection, offers IP40 from front panel and IP20 for terminals



General Information

Brand	ELKO
Product Type	Power Relay

Technical Attributes

Contact Configuration	3 Changeover/TPDT
Contact Material	AgNi/Silver Alloy
Dielectrical Strength (kV)	4 (Supply-output)
Indication	High Intensity LED
Inrush Current (A)	10A / <3s
Maximum Power Dissipation (W)	3
Minimum Electrical Life	60,000 Operations
Minimum Mechanical Life	30,000,000 Operations
Minimum Switching Time (s)	2
Overvoltage Category	III
Rated Current (A)	8
Rated Frequency (Hz)	50/60
Switching Voltage (V)	250V AC / 24V DC
Voltage Range AC/DC (V)	Supply Terminals A1 - A2: 12 - 240V AC/DC

Physical Attributes

Ambient Temperature Range (°C)	-20 to 55
Mounting Type	DIN Rail
Storage Temperature Range (°C)	-30 to 70

Dimensions

Dimensions (mm)	17.6W x 90H x 64D
Weight (g)	80

Protection & Standards

Degree of Protection	Front Panel: IP40, Terminals: IP20
Pollution Degree	2
Standards and Approvals	EN 60669-1, EN 60669-2-1

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------