

Product No: OT1250E03CP

ABB OT1250E03CP CHANGE-OVER SWITCH OT1250E03CP

FEATURES

- High current capacity, making it suitable for applications with high electrical demands
- Robust and secure handle design featuring padlockable positions for added safety
- Mechanism at the end of the switch
- Convenient front operation



General Information	
Brand	ABB
Product Type	Manual
Suitable For	Distribution Board Installation
Туре	Main Switch

Technical Attributes	
Conventional Free-Air Thermal Current - Ith (A)	1250
Indication	I-O-II
Maximum Operational Voltage AC (V)	1000
Mode of Operation	Front
No. of Poles	3
No. of Switches	1
Padlockable	Padlockable in O-position
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss (W)	29
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage (V)	1000
Rated Operational Current AC-21A 415V (A)	1250
Rated Operational Current AC-22A 415V (A)	1250
Rated Operational Current AC-23A 380-415V (A)	1250
Rated Operational Current AC-23A 415V (A)	1250
Rated Operational Power AC-23A 380-415V (kW)	710
Rated Operational Power AC-23A 415V (kW)	710
Rated Operational Voltage (V)	1000



Technical Attributes	
Rated Operational Voltage AC (V)	415
Rated Short-Time Withstand Current - Icw (kA)	50
Terminal Type	Bolt
Transition Type	Open

Physical Attributes	
Control Element Colour	Black
Handle Type	Pistol
Included	Handle, Shaft
Interlockable	Yes
Mounting Type	Front Mount 4-hole

Dimensions	
Dimensions (mm)	400W x 306H x 309D
Weight (kg)	48

Protection & Standards		
Degree of Protection	IP20	
NEMA Degree of Protection	1	
Pollution Degree	3	

Resources	
Product catalogue (Flipbook)	Download from here