

Product No: 942 170-067

HIRSHMANN 4X GIG SFP, 20X GIG TX, 12-24 V DC, 0 °C TO +60 °C, HIOS L2S 942170067

FEATURES

- Store and Forward Switching Mode
- Fanless design
- Ethernet/Fast-Ethernet Switch



General Information

Brand	HIRSHMANN
Product Type	Managed
Series	BOBCAT

Technical Attributes

Communication	Ethernet (20 X GE TX + 2 x GE SFP Slot (Uplink 1) + 2 x GE SFP Slot (Uplink 2))
Electromagnetic Capability	10 V/m (80-2000 MHz) 5 V/m (2000-2700 MHz) 3 V/m (5100-6000 MHz)
Electrostatic Discharge (kV)	6 kV Contact Discharge, 8 kV Air Discharge
Rated Operational Voltage DC (V)	2 x (12 -24)
Resistance to Vibrations	5 Hz ... 8,4 Hz with 3,5 mm amplitude 2 Hz ... 13,2 Hz with 1 mm amplitude 8,4 Hz ... 200 Hz with 1 g 13,2 Hz ... 100 Hz with 0,7 g
Surge Voltage (kV)	Power Line: 2 kV (Line/Earth) and 1 kV (Line/Line); Data Line: 2 kV
Transition Type	2 kV Power Line, 2 kV Data Line

Physical Attributes

Mounting Type	DIN Rail
Operational Temperature Range (°C)	0 to +60
Relative Humidity	1- 95 %

Dimensions

Cable Length (m)	0 - 100
------------------	---------

Protection & Standards

Degree of Protection	IP30 (Housing)
----------------------	----------------

Standards and Approvals	CE, FCC, EN 61131-2, EN 62368-1, cUL 61010-2-201
-------------------------	--------------------------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------