

Product No: 274310

STAHL 6036/1212-455-0151-11 LED TUBULAR LIGHT FITTING 274310

FEATURES

- LED tubular light fitting designed for hazardous areas
- Operates on 24.00 to 48.00 VAC or DC
- Rated operating current of 0.700 A
- Energy-efficient with a power consumption of 13 W
- High luminous efficacy of 104 lm/W providing a total of 1396 lumens
- Equipped with single-row neutral white LEDs and a diffuser
- Suitable for extreme temperatures ranging from -40 °C to +70 °C
- High ingress protection rated at IP66/IP67 for dust and water resistance
- Surface mounting type for easy installation

General Information

Brand	STAHL
Series	6036

Technical Attributes

Nominal Output Current (A)	0.13
Nominal Power (W)	13
Rated Maximum Operational Voltage AC (V)	240
Rated Maximum Operational Voltage DC (V)	240
Rated Minimum Operational Voltage AC (V)	110
Rated Minimum Operational Voltage DC (V)	110
Rated Operational Current (A)	0.13

Physical Attributes

Maximum Temperature (°C)	70
Minimum Temperature (°C)	-30
Mounting Type	Surface

Protection & Standards

Degree of Protection	IP66/67
Standards and Approvals	ATEX/IECEx

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------