


Product No: RH4B-ULD-DC24

IDEC RELAY 4PDT 10A W/DIODE LIGHT RELAY RH4B-ULD-DC24

FEATURES

- 24V DC compatibility for industrial use
- 4DPDT configuration for versatile switching
- Bright LED indicator for clear visual feedback
- Robust 10A contact rating for reliability
- RoHS compliant and durable for industrial applications



General Information

Brand	IDEC
Product Type	Compact
Relay Options	Indicator Light & Diode

Technical Attributes

Coil Voltage DC (V)	24
Contact Configuration	4PDT
Contact Material	Silver Cadmium Oxide
Contact Resistance (mΩ)	50
Contacts	4PDT
Insulation Resistance (MΩ)	100
Minimum Electrical Life	200,000 Operations
Minimum Mechanical Life	50,000,000 Operations
No. of Poles	4
Operating Time	25ms (Measured at the rated voltage (at 20°C))
Power Consumption (VA)	AC: 2.5VA (50Hz), 2VA (60Hz)
Power Consumption (W)	DC: 1.5W
Rated Current (A)	10
Resistance to Shock (m/s ²)	1000
Resistance to Vibrations	10 to 55Hz
Terminal Type	Blade

Physical Attributes

Ambient Temperature Range (°C)	-25 to 70
Operating Humidity	45 to 85% RH (No Condensation)
Terminal Shape	Blade Terminal

Dimensions

Dimensions (mm)	41W x 42H x 27.5D
Weight (g)	74

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------