

## Product No: 110100213TA0N401000

BD SENSORS DMP331 INDUST RIAL PRESSURE TRANSMITTERDMP331 INDUST RIAL PRESSURE T RA 110100213T A0N401000

## FEATURES

- Perfect thermal behaviour.
- Excellent long term stability.
- Pressure port G  $1/2^{"}$  flush from 100 mbar.

General Information	
Brand	BDSENSORS
Product Series	DMP 331
Product Type	Stainless Steel Sensor
Version	Standard

Technical Attributes	
Accuracy	Standard for pN ≥ 0.4 bar: 0.35 % FSO
Application	Plant and machine engineering. Environmental engineering (water - sewage - recycling). Energy industry.
Electrical Connection	Cable outlet with PVC cable (IP67) [Standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 70°C), others on request]
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326.
Input Pressure (bar)	10
Mechanical Connection	1/4" NPT
Mechanical Stability	Vibration: 10 g RMS (25 2000 Hz) according to DIN EN 60068-2-6. Shock: 500 g / 1 msec according to DIN EN 60068- 2-27.
Operational Life	100 million load cycles.
Output Signal	4 20 mA / 2-wire



Permissible Temperatures	Medium: -40 125 °C Electronics / Environment: -40 85 °C Storage: -40 100 °C
Response Time (ms)	≤ 10
Seals	FKM

## Resources

Product catalogue (Flipbook)

Download from here