

Product No: OTM1600E4CM230C

ABB OTM1600E4CM230C MOTORIZED C/O SWITCH OTM1600E4CM230C

FEATURES

- Black Colour handle is directly mounted for easy manual operation
- The fourth pole located on the right side operates in a switched mode with a simultaneous function
- Mechanism at the end of the switch
- Comprehensive hardware kit



General Information

Brand	ABB
Product Type	Manual
Suitable For	Distribution Board Installation
Type	Main Switch

Technical Attributes

Fourth Pole Type	Switched-simultaneous Function
Integrated Motor Drive	Yes
Maximum Operational Voltage AC (V)	1000
No. of Poles	4
No. of Switches	1
Power Loss (W)	48
Rated Operational Current AC-21A 415V (A)	1600
Rated Operational Current AC-22A 415V (A)	1600
Rated Operational Current AC-22A 500V (A)	1600
Rated Operational Current AC-23A 380-415V (A)	1600
Rated Operational Current AC-23A 415V (A)	1600
Rated Operational Current AC-23A 500V (A)	1600
Rated Operational Power AC-23A 380-415V (kW)	710
Rated Operational Voltage (V)	1000
Rated Short-Time Withstand Current - I _{cw} (kA)	50
Rated Short-time Withstand Current - I _{cw} (kA/1s)	50
Transition Type	Open

Physical Attributes

Control Element Colour	Black
Handle Colour	black
Interlockable	Yes
Mounting Type	Front Mount 4-hole

Dimensions

Dimensions (mm)	587W x 372H x 372D
-----------------	--------------------

Protection & Standards

Degree of Protection	IP20
NEMA Degree of Protection	1