


ABB E6H450WOCM30K ACB E6.2H In=5000A 4P 100kA W/D EKIP TOUCH LSIG C/W FIXED PART, SHUNT OPENING/CLOSING 30VAC/DC WITH MOTOR OPERATOR

E6H450WOCM30K



GENERAL INFORMATION

Brand	ABB
Product Type	Automatic
Version	Withdrawable

TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - I _{cu} (kA)	100
G (0.1 to 1 x I _n) - I ₄ (A)	500-5000
I (1.5 to 15 x I _n) - I ₃ (A)	7500-75000
L (0.4 to 1 x I _n) - I ₁ (A)	2000-5000
No. of Poles	4P
Power Loss (W)	850
Rated Current (A)	5000
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - I _{cw} (kA/1s)	100
Rated Uninterrupted Current - I _u (A)	5000
S (0.6 to 10 x I _n) - I ₂ (A)	3000-50000
Terminal Type	HR-HR
Trip Unit	EKIP Touch LSIG



DIMENSIONS

Frame Size	E6.2
------------	------

PROTECTION & STANDARDS

Standards and Approvals	IEC
-------------------------	-----
