

PRODUCT-DETAILS

# CAT4-11M

## CAT4-11M Auxiliary Contact / Coil Terminal Block



### General Information

Extended Product Type	CAT4-11M
Product ID	1SBN010151R1111
EAN	3471523130074
Catalog Description	CAT4-11M Auxiliary Contact / Coil Terminal Block
Long Description	CAT4-11M is a 2-pole side mounted auxiliary contact block with A1 / A2 coil terminal connection on front face, equipped with screw terminals. CAT4-..M version offers terminal assortment matching the marking of 3-pole AF(C)09..16(Z)(B)-30-10 contactors. CAT4-11M is available with 1 N.O. and 1 N.C. instantaneous contacts for standard industrial environments.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Product Main Type	Accessories for Block Contactors

### Popular Downloads

Instructions and Manuals	1SBC101041M6801
CAD Dimensional	2CDC001079B0201

## Drawing

---

**Dimensions**


---

Product Net Width	45 mm
Product Net Depth / Length	31.6 mm
Product Net Height	43 mm
Product Net Weight	0.04 kg

---

**Technical**


---

Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>
Maximum Electrical Switching Frequency	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Mounted Auxiliary Contacts	1 NO, 1 NC
Mounting Type	Front mounting
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Poles	2
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage ( $U_{imp}$ )	6 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 ( $I_{\theta}$ )	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Operational Current DC-13 ( $I_{\theta}$ )	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Voltage	Auxiliary Circuit 690 V

Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 0.1 s 140 A for 1 s 100 A
---	----------------------------------

Standards	IEC/EN 60947-5-1, UL 60947-5-1, CSA C22.2 No. 60947-5-1-14
-----------	--

Suitable For	AF09 AF09Z AF12 AF12Z AF16 AF16Z AFC09 AFC12 AFC16 AF09B AF09ZB AF12B AF12ZB AF16B AF16ZB
Terminal Type	Screw Terminals
Tightening Torque	Auxiliary Circuit 1.2 N·m Control Circuit 1.2 N·m
Wire Stripping Length	Auxiliary Circuit 10 mm Control Circuit 10 mm

## Technical UL/CSA

Connecting Capacity Auxiliary Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Connecting Capacity Control Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Pilot Duty UL/CSA	A600 Q600
Tightening Torque UL/CSA	Auxiliary Circuit 11 in·lb Control Circuit 11 in·lb

## Environmental

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Conventional Free-air Thermal Current ( $I_{th}$ )	acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 16 A
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Certificates and Declarations

ABS Certificate	ABS_20-2060694-PDA
BV Certificate	BV_2634H24900C0

CB Certificate	CB_SE-93053
CCC Certificate	CCC_2013010304651497
CQC Certificate	CQC2013010304651497
Declaration of Conformity - CCC	2020980304001259
Declaration of Conformity - CE	1SBD250007U1000
Declaration of Conformity - UKCA	1SBD250038U1000
DNV Certificate	DNV_TAE00001BV-5
EAC Certificate	EAC_RU C-FR ME77 B03391
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
LR Certificate	LRS_LR2002723TA-02
RINA Certificate	RINA_ELE084013XG
RMRS Certificate	RMRS_1802703280
UL Certificate	UL-US-L252354-131-82119002-6 UL-CA-L252354-331-82119002-5
UL Listing Card	UL_E252354

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	46 mm
Package Level 1 Depth / Length	46 mm
Package Level 1 Height	46 mm
Package Level 1 Gross Weight	0.04 kg
Package Level 1 EAN	3471523130074
Package Level 2 Units	box 192 piece
Package Level 2 Gross Weight	7.68 kg
Package Level 3 Units	4608 piece

## Classifications

eClass	V11.0 : 27371302
E-Number (Finland)	3706509
E-Number (Sweden)	3211431
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block
Object Classification Code	K
UNSPSC	39121522

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

