

Product No: 250600115100N00312000

BD SENSORS DMK331 INDUSTRIAL PRESSURE TRANSMITTER DMK331 INDUSTRIAL PRESSURE TRA 250600115100N00312000

FEATURES

- Pressure port G 1/2" flush for pasty
- and polluted media.
- Pressure port G 1/2" open port PVDF for aggressive media.

| General Information | |
|---------------------|----------------|
| Brand | BD SENSORS |
| Product Series | DMK 331 |
| Product Type | Ceramic Sensor |
| Version | Standard |

| Technical Attributes | |
|-----------------------|--|
| Accuracy | 0.5 % FSO |
| Application | Plant and machine engineering. Energy industry. Environmental engineering (water - sewage - recycling). Medical technology (Specially for oxygen application). |
| Electrical Connection | Male and female plug ISO 4400 |
| Electrical Protection | Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326. |
| Input Pressure (bar) | 6.0 |
| Mechanical Connection | 1/2" NPT |
| Mechanical Stability | Vibration: 10 g RMS (25 2000 Hz) according to DIN EN 60068-2-6. Shock: 500 g / 1 msec according to DIN EN 60068-2-27. |
| Operational Life | 100 million load cycles |
| Output Signal | 4 20 mA / 2-wire |



| Permissible Temperatures | Medium: -40 125 °C Electronics / Environment: -40 85 °C Storage: -40 100 °C |
|--------------------------|---|
| Pressure Port | Stainless steel 1.4404 (316L) |
| Response Time (ms) | ≤ 10 |
| Seals | EPDM (Possible for nominal pressure ranges p N ≤ 160 bar) |

| Physical Attributes | |
|---------------------|---------------------|
| Diaphragm Material | Ceramics Al2O3 96 % |

| Resources | |
|------------------------------|---------------------------|
| Product catalogue (Flipbook) | <u>Download from here</u> |