

## ABB BW340TPN POLYCARBONATE ENCLOSED SWITCH DISCONNECTOR 40A 3P SIDE OPERATED

BW340TPN

### FEATURES

- Polycarbonate enclosure IP65
- One padlockable, Side-operated
- N-, PE-terminals included
- Grey enclosure



### GENERAL INFORMATION

Brand	ABB
Product Type	Enclosed

### TECHNICAL ATTRIBUTES

Conventional Free-Air Thermal Current - I <sub>th</sub> (A)	40
Conventional Thermal Current - I <sub>the</sub> (A)	40
No. of Poles	3P
Rated Current (A)	40
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	690
Rated Operational Current AC-22A 380-415V (A)	40
Rated Operational Current AC-22A 690V (A)	25
Rated Operational Current AC-23A 380-415V (A)	25
Rated Operational Current AC-23A 500V (A)	25
Rated Operational Current AC-23A 690V (A)	16
Rated Operational Power AC-23A 380-415V (kW)	11
Rated Operational Power AC-23A 500V (kW)	11
Rated Operational Power AC-23A 690V (kW)	11
Rated Operational Voltage (V)	690

### PHYSICAL ATTRIBUTES

Colour	Light Grey
--------	------------

**PHYSICAL ATTRIBUTES**

Enclosure Material	Plastic
Handle Colour	Dark Grey
Handle Type	Side-Operated
Included	Handle

**DIMENSIONS**

Cable Cross Section (mm <sup>2</sup> )	0.75-10
Dimensions (mm)	138W X 168H X 68D

**PROTECTION & STANDARDS**

Degree of Protection	IP65
Impact Resistance Rating	Housing IK08
Standards and Approvals	IEC 60947-1, IEC 60947-3

**RESOURCES**

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------