

Product No: 471600013100M00112000

BD SENSORS LMK351 SCREW-IN TRA NSMITTER LMK351 SCREW-IN TRANSMITTER 471600013100M00112000

FEATURES

- Pressure port PVDF-version for aggressive media.
- Pressure port G 1 1/2" for pasty and polluted media.



| General Information | |
|---------------------|---|
| Brand | BDSENSORS |
| Product Series | LMK 351 |
| Product Type | Ceramic Sensor |
| Suitable For | Fuel and oil. Viscous and pasty media. |
| Version | Standard |

| Technical Attributes | |
|--------------------------|--|
| Accuracy | 0.35 % FSO |
| Application | Plant and machine engineering. Environmental engineering (water – sewage – recycling). |
| Electrical Connection | Male and female plug ISO 4400 |
| Electrical Protection | Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326. |
| Mechanical Connection | G11/2" DIN 3852 with flush sensor. |
| Mechanical Stability | Vibration: 10 g RMS (20 2000 Hz) according to DIN EN 60068-2-6. Shock: 100 g / 1 msec according to DIN EN 60068-2-27. |
| Operational Life | 100 million load cycles. |
| Output Signal | 4 20 mA / 2-wire |
| Permissible Temperatures | Medium: -40 125 °C Electronics / Environment: -40 85 °C |



| | Storage: -40 100 °C |
|------------------------------|--|
| Pressure (mH ₂ O) | 6.0 |
| Pressure Port | Stainless steel 1.4404 (316L) |
| Response Time (ms) | Mean response time: ≤ 200 Max. response time: 380 |
| Seals | FKM |

| Physical Attributes | |
|---------------------|---------------------|
| Diaphragm Material | Ceramics Al2O3 96 % |
| | |

| Resources | |
|------------------------------|--------------------|
| Product catalogue (Flipbook) | Download from here |