

Product No: 101107771

SCHMERSAL BPS33 SAFETY SENSOR 101107771

FEATURES

- Safety sensor with thermoplastic enclosure
- Features coding and requires a prerequisite evaluation unit
- Equipped with 1 opener and 1 shutter
- Actuating element is a magnet
- Comes with a terminal connector cable, 1 meter in length
- Lateral active area for operation
- Switching voltage rated at 100 V AC/DC
- Switching current of 0.4 A
- Switching capacity of 10 W



Note: In case of failure (interruption of the 0 V supply) the maximum leakage current is 1 mA.

General Information	
Brand	SCHMERSAL
Cable Note	All indications including the conductor ferrules.
Coding Level According to EN ISO 14119	Low
EAN	4030660000000
eCl@ss Number, Version 11.0	27-37-12-11
eCl@ss Number, Version 9.0	27-37-12-11
ETIM 6.0	EC000223
ETIM 7.0	EC000641
Housing Construction Form	Norm construction design
Product Type	Safety Sensor
Protection Class of Operating Resource	3
Recommended Actuator	AZM 40-B1
Recommended Safety Switchgear	SRB 202C SRB 211AN SRB 400C
Series	BPS33
Working Principle	Electromechanical

Technical Attributes

No. of Auxiliary Contacts	1
Contact Material	Silver
Design of Control Element	Short-circuit proof, p-type
Latching Force (N)	30
Maximum Actuating Speed (m/s)	2
Maximum Bounce Duration (ms)	2
Maximum Cable Cross Section (mm ²)	2.5
Maximum Fuse Rating	6 A gG D-fuse
Maximum Switching Capacity (W)	0.24
Minimum Actuating Speed (mm/min)	10
Minimum Cable Cross Section (mm ²)	0.75
Minimum Mechanical Life	30000 Operations
Minimum Positive Break Force (N)	20
No. of Safety Contacts	1
Overvoltage Category	3
Positive Break Travel (mm)	8
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	300
Rated Operating Current (mA)	50
Rated Short-circuit Current (A)	400
Resistance to Shock (g/ms)	30 / 11
Switching Element	Opener (NC)
Switching Principle	Slow action
Terminal Type	Flat plug-in connector - 6.3 mm x 0.8 mm / 2 x 2.8 mm x 0.8 mm
Thermal Test Current (A)	0.25
Utilisation Category	DC-13 AC-15

Physical Attributes

Actuator Type	Magnet
Enclosure Coating Material	Painted
Enclosure Material	Plastic, glass-fibre-reinforced

Gross Weight (g)	75
Installation Conditions	Quasi-flush
Maximum Ambient Temperature (°C)	70
Minimum Ambient Temperature (°C)	0
Mounting Type	Can be clipped into standard rail
Net Weight (g)	59
Storage Temperature (°C)	-25 to 70
Wire Cross-Section	0.25 mm

Dimensions

Cable Length (m)	2
Depth (mm)	220
Height (mm)	100
Sensor Height (mm)	90
Sensor Length (mm)	33
Width (mm)	40

Protection & Standards

Degree of Protection	IP67 / IP65
Pollution Degree	2
Standards	EN IEC 60947-5-1

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------