



PRODUCT-DETAILS

T4V 250 TMA 100-1000 3p F F 1150V AC

T4V 250 TMA 100-1000 3p F F 1150V AC

---

### General Information

Extended Product Type	T4V 250 TMA 100-1000 3p F F 1150V AC
Product ID	1SDA064208R1
EAN	8015644670825
Catalog Description	T4V 250 TMA 100-1000 3p F F 1150V AC
Long Description	C.BREAKER TMAX T4V 250 1150V AC FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 100-1000 A

---

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

---

### Environmental

Environmental Information	9AKK10103A1057 9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---

**Ordering**


---

EAN	8015644670825
Minimum Order Quantity	1 piece
Customs Tariff Number	85352100

---



---

**Dimensions**


---

Product Net Width	105 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	2.35 kg

---



---

**Container Information**


---

Package Level 1 Units	1 piece
Package Level 1 Width	228 mm
Package Level 1 Height	244 mm
Package Level 1 Depth / Length	286 mm
Package Level 1 Gross Weight	2.5 kg
Package Level 1 EAN	8015644670825

---



---

**Additional Information**


---

Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 5.2 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current ( $I_n$ )	100 A
Rated Operational Voltage	1150 V AC 1000 V DC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(1000 V AC) 12 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(415 V AC) 200 kA (1000 V AC) 20 kA
Rated Uninterrupted Current ( $I_u$ )	250 A
Release	TMA
Release Type	TM
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	T4
Terminal Connection Type	Fixed Circuit-Breakers Front
Version	F

---



---

**Certificates and Declarations**


---

Data Sheet, Technical Information	1SDC210300D0201
Declaration of Conformity - CE	9AKK106713A5540

---

GL Certificate

1SDL000163R0061

Instructions and Manuals1SDH000457R0001

---

## Classifications

---

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T