

ABB E12N3ETG16W ACB E1.2N 3P 66KA WITHDRAWABLE 1600A EKIP TOUCH LSIG

E12N3ETG16W



GENERAL INFORMATION

Brand	ABB
Product Type	Automatic
Version	Withdrawable

TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - Icu (kA)	66
G (0.1 to 1 x In) - I4 (A)	160-1600
I (1.5 to 15 x In) - I3 (A)	2400-24000
L (0.4 to 1 x In) - I1 (A)	640-1600
No. of Poles	3P
Power Loss (W)	400
Rated Current (A)	1600
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - Icw (kA/1s)	50
Rated Uninterrupted Current - Iu (A)	1600
S (0.6 to 10 x In) - I2 (A)	960-16000
Terminal Type	HR-HR
Trip Unit	EKIP Touch LSIG



DIMENSIONS

Frame Size	E1.2
------------	------

PROTECTION & STANDARDS

Standards and Approvals	IEC
-------------------------	-----

RESOURCES

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------