

Product No: MS116-25

ABB MS116-25 MANUAL MOTOR STARTER 20 ... 25 A MS116-25

FEATURES

- Compact design, ideal for installations with limited space
- Provides reliable protection against short-circuits, overload and phase failures
- High breaking capacity
- Features a lockable rotary handle with clear switch position indication
- Suitable for both 3 phase and single phase applications



General Information	
Brand	ABB
Product Type	Manual Motor Starter

Technical Attributes	
Design of Control Element	Turn Button
Breaking Capacity 400V AC - Icu (kA)	16
Main Circuit Electrical Connection	Screw Connection
No. of Poles	3
Overload Release Current Setting (A)	20
Phase Failure Sensitive	Yes
Power Loss (W)	8.4
Rated Instantaneous Short-Circuit Current - Ii (A)	375
Rated Insulation Voltage (V)	690
Rated Operational Current (A)	10
Rated Operational Power AC-3 400V (kW)	11
Rated Operational Voltage (V)	690
Rated Uninterrupted Current - Iu (A)	25
Switching Type	Thermomagnetic
Terminal Type	Screw Terminals
Thermal Current Setting Range (A)	20.0 - 25.0



Thermal Overload Protection	Yes
-----------------------------	-----

Dimensions	
Dimensions (mm)	45W x 97.8H x 85.4D

Protection & Standards	
Degree of Protection	IP20

Resources	
Product catalogue (Flipbook)	Download from here